

MIGHTY SPARKLETM DIANOND, 18 DURABLE, LOW-MAINTENANCE FLOOR FINISH

- 18% solids formulation provides high initial gloss
- Maintains shine and durability in low-maintenance applications
- Low-odor formulation for anytime application
- Use with State JetSet for easy application





CARE FOR WORK ENVIRONMENTS[®]

MIGHTY SPARKLE[™] DIAMOND,18

LOW-MAINTENANCE SOLUTION

Mighty Sparkle Diamond Pro 18 is the solution for facilities that want high shine and durability, but do not have the capability to perform routine floor maintenance such as buffing and burnishing. Diamond Pro's 18% solids formula will maintain its high initial gloss while resisting scuff marks, black heel marks, and water spots making it ideal for high-traffic areas. Use on all resilient floors including vinyl, vinyl composition (VCT), vinyl asbestos, asphalt tile, rubber and linoleum. This product can also be used on on Terazzo flooring. Diamond Pro 18 is a low odor formula, so it can be applied during normal business hours.

DIRECTION FOR USE

Please review label and SDS for all product directions, precautions and first aid information prior to using this product.

- 1. Only for use indoors. Do not apply if floor temperature is less than 55°F.
- 2. Strip floor using one of State's strippers according to label directions.
- 3. Apply 3-5 thin coats using a clean applicator. If a higher gloss is desired, apply additional coats. Allow 45-60 minutes drying time between coats.

Note: This product is a self-sealing finish, however if tile is old, worn or porous, initially applying 1-2 coats of State's Sealer will enhance gloss and long term performance.

Coverage: 2,000 - 3,000 square feet per gallon depending on application method and porosity of floor.

MAINTENANCE

Mighty Sparkle Diamond Pro 18 is a low-maintenance floor finish that does not need to be buffed or burnished, however, to enhance and restore appearance of finish, low-speed buffing and high-speed burnishing equipment can be used.

- 1. Dust mop or sweep floor.
- 2. Clean floor using one of State's neutral floor cleaners according to label directions.
- 3. If low-speed buffing is desired, use one of State's floor restorer or spray buff products according to label instructions as well as the appropriate floor machine pad.
- 4. If high-speed burnishing is desired, use one of State's floor restorer products according to label instructions as well as the appropriate floor machine pad.

INTERIM MAINTENANCE

Mighty Sparkle Diamond Pro 18 can be applied as a top coat finish to existing acrylic, cross-linked polymer finishes which includes all other State floor finishes. To perform a scrub and recoat, use the following procedure:

- 1. Dust mop or sweep.
- 2. Deep scrub using one of State's deep scrub cleaners.
- 3. Using a clean applicator, apply 1-2 coats of Diamond Pro 18 floor finish.

TECHNICAL DATA

Appearance: Milky white emulsion Odor: Minimal, characteristic pH: 7.5-8.5 Slip Resistance: 0.5 minimum (ASTM D2047) Solids Content: 18% Polymer Type: Modified Acrylic

PACKAGING	
126241	GL4
126242	D5
126243	D20
126321	D55



Canada 6935 Davand Drive Mississauga, Ontario L5T 1L5 Puerto Rico

Royal Industrial Park, Bldg "M" Local #5, Carr 869, km 1.5 Palmas Cataño, P.R. 00962 To Order Call: 787-275-3185



© Copyright 2021 - State Industrial Products Corp.

To Order Call: 1-800-668-6513