INDUSTRIAL LUBRICANTS Solutions



- Silicone formula creates non-stick surface
- Excellent release agent
- Bulk dries in minutes; dry spray aerosol





MULTI-PURPOSE:

- Waterproofs
- Rust proofs
- Stops squeaks

- Lubricates
- Protects
- Prevents sticking

EXCELLENT RELEASE AGENT

SPW is formulated with viscous silicones to provide superior lubrication with excellent release properties.

SAFE ON MOST SURFACES

Apply SPW to almost any surface. One application dries in minutes.

PREVENTS RUSTING

Exclusive corrosion inhibitors in SPW leave surfaces coated and protected as well as lubricated. The SPW coating is formulated for longer-lasting protection.

NONSTAINING

Provides a colorless film that resists sticking of snow, grass, clippings, sawdust and other residues.

SILICONE PROTECTIVE COATING FOR:

- Pulleys
- Conveyor Rollers
- Presses
- Snow Plow Blades
- Grader Blades
- Grass Cutters
- Hoes
- Lift Truck Chain Area
- Dock Door Run Channels
- Hoist or Lift Cranes
- Elevator Pulleys
- · Assembly & Feed Tables
- Looms
- Delivery Troughs
- Drawer & Files

TECHNICAL DATA:

APPEARANCE: clear amber liquid

ODOR: mild solvent

FLASH POINT (BULK): 103°F by TCC

FLASH POINT (AEROSOL): extremely flammable aerosol

SOLVENT BASE: yes

DRY TIME: aerosol - dry spray; bulk - 10-20 minutes STABILITY TO MINUS 30 DEGREES F.: will not freeze

SHELF STABILITY: minimum one year

PACKAGING

25401 55 GL Drum 25405 20 GL Drum 1 GL Bottle/CS4 125599 43040 11.5 OZ Aerosol/CS12 105462 11.5 OZ Aerosol/CS24



5915 Landerbrook Drive Mayfield Heights, OH 44124 To Order Call: 1-866-747-2229 www.stateindustrial.com

Canada

6935 Davand Drive Mississauga, Ontario L5T 1L5 To Order Call: 1-800-668-6513

Puerto Rico

Royal Industrial Park, Bldg "M" Local #5, Carr 869, km 1.5 Palmas Cataño, P.R. 00962 To Order Call: 787-275-3185





