

FLOOR CARE *Solutions*



MIGHTY SPARKLE™ DIAMOND *Pro* 22

**VERSATILE, LOW-MAINTENANCE
FLOOR FINISH**



- 22% solids formulation for high initial and sustained gloss
- Responds well to buffing and burnishing for better shine and durability
- Maintains shine and durability in low-maintenance applications
- Low-odor formulation for anytime application



CARE FOR WORK ENVIRONMENTS®

MIGHTY SPARKLE™ DIAMOND Pro 22

VERSATILE FLOOR FINISH

Mighty Sparkle Diamond Pro 22's 22% solids formulation provides superior initial and sustained gloss and durability in low or routine maintenance applications. With daily mopping or autoscrubbing, Diamond Pro 22 resists scuffing and marking to retain gloss and durability reducing the need for more costly, time consuming floor maintenance. For facilities that do occasional buffing and burnishing, Diamond Pro 22 will respond with an enhanced gloss and durability prolonging the life of the floor finish.

Diamond Pro 22 applies easily with all types of applicators. Use on all resilient floors including vinyl, vinyl composition (VCT), asphalt tile, rubber and linoleum. This product can also be used on Terazzo flooring. Diamond Pro 22 is a low-odor formula, so it can be applied during normal business hours.

DIRECTION FOR USE

Please review label and SDS for all product directions, precautions and first aid information prior to using this product.

1. Only for use indoors. Do not apply if floor temperature is less than 55°F.
2. Strip floor using one of State's strippers according to label directions.
3. Apply 3-5 thin coats using a clean applicator. If a higher gloss is desired, apply additional coats. Allow 45-60 minutes drying time between coats.

Note: This product is a self-sealing finish, however if tile is old, worn or porous, initially applying 1-2 coats of State's sealer will enhance gloss and long term performance.

Coverage: 2,000 - 3,000 square feet per gallon depending on application method and porosity of floor.

MAINTENANCE

Mighty Sparkle Diamond Pro 22 is a low-maintenance floor finish that does not need to be buffed or burnished regularly, however, to enhance and restore appearance of finish, low-speed buffing and high-speed burnishing equipment can be used.

1. Dust mop or sweep floor.
2. Clean floor using one of State's neutral floor cleaners according to label directions.
3. If low-speed buffing is desired, use one of State's floor restorer or spray buff products according to label instructions as well as the appropriate floor machine pad.
4. If high-speed burnishing is desired, use one of State's floor restorer products according to label instructions as well as the appropriate floor machine pad.

INTERIM MAINTENANCE

Mighty Sparkle Diamond Pro 22 can be applied as a top coat finish to existing acrylic, cross-linked polymer finishes which includes all other State floor finishes. To perform a scrub and re-coat, use the following procedure:

1. Dust mop or sweep.
2. Deep scrub using one of State's deep scrub cleaners.
3. Using a clean applicator, apply 1-2 coats of Diamond Pro 22 floor finish.

TECHNICAL DATA

Appearance: Milky white emulsion

Odor: Minimal, characteristic

pH: 7.5-8.5

Slip Resistance: 0.5 minimum (ASTM D2047)

Solids Content: 22%

Polymer Type: Modified Acrylic

PACKAGING

126245	GL4
126246	D5
126247	D20
126322	D55



State Industrial Products
5915 Landerbrook Drive
Mayfield Heights, OH 44124
To Order Call: 1-866-747-2229
www.stateindustrial.com

Canada
6935 Davand Drive
Mississauga, Ontario L5T 1L5
To Order Call: 1-800-668-6513

Puerto Rico
Royal Industrial Park, Bldg "M"
Local #5, Carr 869, km 1.5 Palmas
Cataño, P.R. 00962
To Order Call: 787-275-3185

