

# WATER TREATMENT *Solutions*



## COIL COMMANDO™

FOAMING ALKALINE COIL CLEANER



- Powerful alkaline formula removes oxidation, grease, and dirt from air conditioning coils
- Brightens weathered aluminum and restores it to a bright, shiny luster without streaking
- Concentrated formula can be diluted for economical use



CARE FOR WORK ENVIRONMENTS®

# COIL COMMANDO™

## FOAMING ALKALINE COIL CLEANER

### CLEANS AIR CONDITIONING COILS

Coil Commando™ Foaming Coil Cleaner removes oxidation from air conditioning coils. Coil Commando also keeps coils free of insulating deposits by emulsifying grease, keeping air conditioners running properly and efficiently.

### EXPANDING FOAMING ACTION

Coil Commando's expanding, sudsing action penetrates deep into coils, and pushes contamination outward from inside the coil. The extended contact time allows for better cleaning of the aluminum.

### EASY-TO-USE

No scrubbing or pre-cleaning is necessary. Just apply Coil Commando and let it stand for three minutes, then rinse away.

### POWERFUL, NON-ACID FORMULATION

Coil Commando brightens weathered aluminum and removes the toughest dirt, film, diesel smoke and road scum. Aluminum is restored to a bright, shiny luster without streaking, dulling or agitation. Coil Commando's alkaline formula eliminates the concern of working with acids.

### ECONOMICAL

Coil Commando is highly-concentrated and dilutable. It improves the efficiency of air conditioners by keeping coils free of insulating deposits, thus saving energy.

### DIRECTIONS FOR USE

#### AIR CONDITIONER COILS:

Apply Coil Commando at recommended dilution using a pump Sprayer. Thoroughly wet down the coils. Rinse immediately with plenty of water.

**FOR COIL CLEANING:** Use 8 oz. of Coil Commando per gallon of water.

**FOR COIL BRIGHTENING:** Use 15 oz. of Coil Commando per gallon of water.

#### ALUMINUM TRAILERS AND OTHER ALUMINUM SURFACES:

Apply Coil Commando at recommended dilution using a high-pressure washer. Allow the solution to sit for three minutes, then rinse thoroughly with plenty of water.

**FOR BADLY PITTED AND OXIDIZED SURFACES:** Use 18 oz. of Coil Commando per gallon of water. If, after application, the surface does not appear uniform, reapply using 6 oz. of Coil Commando per gallon of water and rinse immediately with plenty of water.

**FOR NORMAL CLEANING AND BRIGHTENING:** Use 6 oz. of Coil Commando per gallon of water.

**FOR LIGHT-DUTY CLEANING:** Use 3 oz. of Coil Commando per gallon of water.

Please review label and SDS for all product directions, precautions and first aid information.

### TECHNICAL DATA

**APPEARANCE:** clear, yellow liquid

**ODOR:** mild

**SPECIFIC GRAVITY:** 1.18

**WEIGHT PER GALLON:** 10.0 lbs.

**pH (CONCENTRATE):** > 13

**FLASHPOINT:** none to boiling point

**DETERGENCY:** excellent

**FOAMING POWER:** optimum

**BRIGHTENING POWER:** excellent

**RINSEABILITY:** excellent

### PACKAGING

122393	20 GL Drum
122392	1 GL Bottle/CS4



**State Industrial Products**  
5915 Landerbrook Drive  
Mayfield Heights, OH 44124  
To Order Call: 1-866-747-2229  
www.stateindustrial.com

**Canada**  
6935 Davand Drive  
Mississauga, Ontario L5T 1L5  
To Order Call: 1-800-668-6513

**Puerto Rico**  
Royal Industrial Park, Bldg "M"  
Local #5, Carr 869, km 1.5 Palmas  
Cataño, P.R. 00962  
To Order Call: 787-275-3185

