

# SPECIALTY *Solutions*



## **Make-A-Bond** Double-Sided Closed-Cell Urethane Adhesive



- Strong Bonding Power – Forms a tenacious bond on a wide variety of smooth, clean surfaces.
- Interior / Exterior Use – Closed cell urethane foam won't absorb water, eliminating freeze/thaw failures.
- Repositionable – final bonding occurs after 3 – 5 minutes, allowing perfect alignment.

**S**tate®  
Since 1911

CARE FOR WORK ENVIRONMENTS®

# Make-A-Bond

## Double-Sided Closed-Cell Urethane Adhesive

### REPOSITIONABLE

Final bonding occurs after three to five minutes, allowing perfect alignment of joined surfaces and reducing errors.

### EXTERIOR AND INTERIOR USE

Make-A-Bond adhesive has closed cell urethane foam so it won't absorb water, unlike open cell products which suffer damage from freeze/thaw cycles.

### IMPACT AND TEMPERATURE RESISTANT

Shocks and slams won't dislodge Make-A-Bond, even in extreme temperatures: -20°F up to 150°F.

### WITHSTANDS GASOLINE AND SOLVENTS

Intermittent contact with gas or solvents will not affect Make-A-Bond.

### STRONG BONDING POWER

The product forms a tenacious bond on a wide variety of smooth, clean surfaces.

### VERSATILE

Make-A-Bond has excellent results on steel, plastic, rubber, smooth painted surfaces, fiberglass, signs, name plates, dispensers, corner protectors, electric wires and cable, carpeting, tile, baseboards, smoke alarms, cork and bulletin boards, mirrors, non-drillable surfaces such as machine tools, automotive parts including body moulding and interior panels.

### DIRECTIONS:

1. Clean surfaces to be bonded
2. Apply Make-A-Bond to one side
3. Remove liner
4. Position item to be bonded
5. Re-align if necessary within two minutes
6. Press firmly into place

Please review label and SDS for all product directions, precautions and first aid information.

### TECHNICAL DATA:

**COLOR:** black  
**ODOR:** none  
**DENSITY:** 33 pounds per cubic foot  
**LENGTH:** 25 foot rolls  
**WIDTH:** 3/4 inch  
**PEEL STRENGTH ON STEEL:** 105 oz./inch  
**TENSILE STRENGTH:** 280psi  
**TEMPERATURE RESISTANCE:** -20°F to 150°F  
**WATER ABSORPTION:** (24 hour immersion) <1%  
**UV LIGHT RESISTANCE:** excellent  
**GASOLINE RESISTANCE:** passes intermittent contact test  
**SHELF LIFE:** minimum one year

## OTHER SPECIALTY SHOP ITEMS




**Knock Out™**  
Aerosol Graffiti and Soil Remover



**RTV™**  
Silicone Adhesive/Sealant/  
Caulk/Gasket Marker



**Formuflex®**  
Clear Adhesive/Sealant  
with Ultra Violet Inhibitor



**Liqua Pads**  
Absorbent Pads for Spills

### PACKAGING

26017 1 Roll/CS4

26018 1 Roll



**State Industrial Products**  
5915 Landerbrook Drive  
Mayfield Heights, OH 44124  
To Order Call: 1-866-747-2229  
www.stateindustrial.com

**Canada**  
6935 Davand Drive  
Mississauga, Ontario L5T 1L5  
To Order Call: 1-800-668-6513

**Puerto Rico**  
Royal Industrial Park, Bldg "M"  
Local #5, Carr 869, km 1.5 Palmas  
Cataño, P.R. 00962  
To Order Call: 787-275-3185