



FUEL FLO

MULTIFUNCTIONAL DIESEL FUEL ADDITIVE

Benefits:

State's Fuel Flo is an ashless multifunctional diesel fuel additive designed to extend injector life and improve fuel economy through the reduction of insoluble gums and improved lubricity in today's low sulfur diesel fuels. The cetane improver in Fuel Flo will extend low temperature startability, improve combustion and over-all cold weather operation. Fuel Flo is formulated with a cold flow modifier to reduce wax formation at low temperatures therefore keeping your fuel flowing freely and not plugging filters in cold weather. Fuels in storage tanks will stay fresher longer with the anti-oxidant in Fuel Flo. Additional benefits include corrosion inhibition and de-emulsification in storage tanks.

Features:

- Improves fuel economy through the reduction of insoluble gums on injectors and provides additional lubricity in low sulfur fuels.
- Provides corrosion protection.
- Improves cold weather performance and provides more complete combustion with cetane improver.
- Extends low temperature operability by modifying wax crystal growth preventing plugging of fuel filters.
- Sheds water from fuels in storage tanks.
- Reduces the oxidation rate of fuels in storage tanks.



FUEL FLO

MULTIFUNCTIONAL DIESEL FUEL ADDITIVE

DIRECTIONS FOR USE:

Fuel tanks should be at least 1/4 full before adding State Fuel Flo.

DIESEL ENGINES - Warm Weather Operations

Add 16 ounces (1 pint) to 125 gallons of fuel or 5 ounces to 40 gallons of fuel.

DIESEL FUEL STORAGE TANKS - Warm Weather Operations

Add 1 gallon to 1000 gallons of diesel pumped into tank.

DIESEL ENGINES - Winter Operations

Double the dosage of Fuel Flo for cold weather protection.

1 quart to 125 gallons of fuel or 10 ounces to 40 gallons of fuel.

DIESEL FUEL STORAGE TANKS - Winter Operations

Add 2 gallons to 1000 gallons of diesel pumped into tank.

Please review label and MSDS for all product directions, precautions and first aid information.

TECHNICAL DATA:

APPEARANCE: Clear amber liquid

ODOR: Solvent

SPECIFIC GRAVITY: 0.795

WEIGHT PER GALLON: 6.63 LBS/GAL

FLASH POINT: 110°F (43.3°C)

RUST AND CORROSION PROTECTION: Excellent

CLEANS FUEL INJECTORS: Yes

IMPROVES FUEL STABILITY: Yes

PREVENTS FORMATION OF WATER

EMULSIONS: Yes

DISPERSES INSOLUBLE GUMS: Yes

COLD FLOW IMPROVEMENT PROPERTIES:

Excellent

MODIFICATION OF WAX CRYSTALS: Yes

This diesel fuel additive complies with the Federal low sulfur content requirements for use in diesel motor vehicles and non-road engines.



State Chemical

5915 Landerbrook Drive
Mayfield Heights, OH 44124
To Order Call: 1-800-782-2436
www.statechemical.com

Canada

6935 Davand Drive
Mississauga, Ontario L5T 1L5
To Order Call: 1-800-668-6513

Puerto Rico

Royal Industrial Park, Bldg "M"
Local #5, Carr 869, km 1.5 Palmas,
Cataño, P.R. 00962
To Order Call: 1-800-782-2436

State Chemical is a Division of State Industrial Products

**60R07
LIT800201**

© Copyright 2006 — State Industrial Products Corp.