

INDUSTRIAL LUBRICANTS *Solutions*



HC OIL

MULTI VISCOSITY HYDRAULIC OIL



- Formulated for high shear stability to stay viscous longer
- Strong film strength prevents water mixing
- Reduces hardening, shrinking and cracking of seals



CARE FOR WORK ENVIRONMENTS®

HC OIL

MULTI VISCOSITY HYDRAULIC OIL

REDUCES DOWNTIME

State HC Oil provides dramatic cost savings with its anti-wear effectiveness. The need for replacement parts is minimized and oil loss from leakage is reduced.

EXTENDS SERVICE LIFE

A quality oil must remain viscous to provide effective lubrication. State HC Oil is formulated for high shear stability to stay viscous longer. Ordinary oils allow water to mix with them. State HC Oil has a strong film strength that prevents water mixing. This extends the service life of the equipment and the oil.

Strong film strength keeps State HC Oil in complete contact with metal surfaces and its anti-rust properties protect equipment.

State HC Oil provides continuous lubrication. High oxidation resistance prevents sludge buildup, extending service life and increasing the amount of time between maintenance shutdowns.

REDUCES INVENTORY

State HC Oil is a 10W40 multi-viscosity oil designed for a wide range of applications. Inventory reduction results in added savings from stocking one product and reducing product application confusion.

EXCELLENT COLD CLIMATE FEATURES

State HC Oil provides protection at temperatures as low as -30°F, allowing for application and service in cold climates. Use State HC Oil as a non-detergent engine oil where SAE 10W40 is specified for winter use.

DIRECTIONS FOR USE

Check high pressure hydraulic systems before working on them to avoid exposure to pressurized oil. HC Oil will provide superior lubrication, as well as a more efficient operation for all types of pumps and hydraulic systems that specify oil viscosities within the range covered by this product (10W40). This eliminates the need for several different weights of hydraulic oil. HC Oil is recommended for all operating conditions not exceeding the specifications of this product. Follow equipment manufacturer's recommended filling and maintenance procedures. For use in compressors, refer to recommendations on the product technical data sheet. Avoid contamination of food during the use and storage of this product.

TECHNICAL DATA

FLASHPOINT: 425°F (218°C)

POUR POINT: -49°F (-45°C)

VISCOSITY INDEX: 151

OTHER STATE INDUSTRIAL LUBRICANT PRODUCTS



Duraflex™
Dry Chain and Cable
Lubricant



Gear Oil
Extreme Pressure Gear
Lubricants



Professional Lubes™
BS-I Grease
High-Temp and Impact
Resistant Grease



Professional Lubes™
XT-S Grease
Extreme Temperature
Versatile Grease

PACKAGING

121041	55 GL Drum
121040	15 GL Drum
121039	5 GL Pail



State Industrial Products
5915 Landerbrook Drive
Mayfield Heights, OH 44124
To Order Call: 1-866-747-2229
www.stateindustrial.com

Canada
6935 Davand Drive
Mississauga, Ontario L5T 1L5
To Order Call: 1-800-668-6513

Puerto Rico
Royal Industrial Park, Bldg "M"
Local #5, Carr 869, km 1.5 Palmas
Cataño, P.R. 00962
To Order Call: 787-275-3185

