

# GROUNDS CARE *Solutions*



## **LIQUA-FIL™** CRACK AND EXPANSION JOINT FILLER



- Ready-to-use formula
- Seals out water
- Expands and contracts as needed



CARE FOR WORK ENVIRONMENTS®

# LIQUA-FIL™

## CRACK AND EXPANSION JOINT FILLER

### READY TO USE

State's Liqua-Fil comes in a one gallon container with a convenient pour spout cap. No mixing or heating is required. Maintenance repairs can be made on the spot.

State's Liqua-Fil prevents crumbling surfaces when used to seal cracks in blacktop, asphalt or concrete. Used soon enough, Liqua-Fil prevents future chuckholes. Easily applied, Liqua-Fil can help avoid costly repairs to vehicles caused by broken paved areas.

### SPECIALLY FORMULATED

State's Liqua-Fil is formulated to fill the deepest part of the crack before it sets up. This ensures that the seal will hold through all types of weather.

The expansion and contraction of freezing and thawing water in paved surfaces can cause the surface to crack and crumble. State's Liqua-Fil prevents water penetration into a sealed crack to fight freeze-thaw damage and avoid further cracking.

### USE INDOOR OR OUTDOOR

Repair any concrete, blacktop or asphalt surface in minutes: inside or outside of warehouses, factories, shipping and receiving dock areas, parking lots and garages; any area that can be damaged by cracks from heavy traffic or temperature changes.

### DIRECTIONS FOR USE

Clean dirt and loose material from crack with a brush, water hose or air pressure. Dampen surface slightly but avoid leaving any standing water in crack when applying State's Liqua-Fil. Do not apply at temperatures below 50° F (10°C), or if rain is forecast.

Turn container over several times to mix contents. Place pour spout cap on gallon container and snip off the top of spout to width of crack to be filled, or as desired. Pour State's Liqua-Fil into crack, pressing sides for even flow.

Fill crack to a level slightly below adjacent surfaces. DO NOT OVERFILL. Allow to set up. To keep from cracking, spread sand over surface.

For extra deep cracks, fill first with sand to within one half inch of surface or apply State's Liqua-Fil in two applications. For the first application, fill to within one-half inch of surface, then apply second application after the first has hardened.

For immediate cleanup, wash tools with water. To remove dried State's Liqua-Fil, wash tools with State's SSD-II.

Please review label and SDS for all product directions, precautions and first aid information.

### TECHNICAL DATA

**APPEARANCE:** black liquid

**ODOR:** mild petroleum

**DRYING TIMES:** 15 minutes to touch; 6 hours to traffic

**COVERAGE:** one gallon covers 50 linear feet, 1 inch deep, 3/8 inch wide, varies with crack size

**FREEZE-THAW STABILITY:** keep uncured product from freezing

**NOTE:** Liqua-Fil should be used within six months of receipt of product.

### PACKAGING

26033

1 GL Bottle/CS6



**State Industrial Products**  
5915 Landerbrook Drive  
Mayfield Heights, OH 44124  
To Order Call: 1-866-747-2229  
www.stateindustrial.com

**Canada**  
6935 Davand Drive  
Mississauga, Ontario L5T 1L5  
To Order Call: 1-800-668-6513

**Puerto Rico**  
Royal Industrial Park, Bldg "M"  
Local #5, Carr 869, km 1.5 Palmas  
Cataño, P.R. 00962  
To Order Call: 787-275-3185

