



Baseboard Stripper

PREPS FOR FLOOR FINISH

The only way to have and maintain a beautiful floor is to have a perfectly clean surface before finishing. SFR baseboard stripper removes soil, wax and floor finish buildup around baseboards, appliances and ceramic wall tiles in corners and other hard-to-reach areas. Thoroughly strips the problem area and leaves it sparkling clean...ready for floor finish.

PENETRATES AND LIQUIFIES

SFR's exclusive formula contains Liquasolv, which breaks the chemical bond that holds the finish to the floor and liquifies it. Special cleaners then penetrate into the microscopic pores of the tile, lift out embedded dirt and polish, and hold them in suspension. Simply scrape and rinse.

CLINGS TO VERTICAL SURFACES

SFR's specially thickened formula allows it to cling to vertical surfaces such as baseboards — preventing runoff and evaporation. The longer it clings, the more thorough the job of stripping.

SPECIAL APPLICATION SYSTEM

The unique valve directs application of SFR down and out in a fan-shaped pattern that is approximately 12" wide, the size of most floor tiles. Ideal for applying on baseboards, under counters, ledges or other inaccessible places.

TIME-RELEASE FORMULA

SFR begins to work on contact. The microscopic bubble action tells you it's working. No more timing, no more guesswork. When the bubbling stops, the job is done.

ELIMINATES EXCESS COSTS

Unlike other floor strippers, SFR has no harsh chemical odors such as ammonia. Our pleasant Morning Fresh™ fragrance allows it to be used during regular business hours. Saves on overtime costs, especially in restaurants, supermarkets and hospitals.



SFR®

Baseboard Stripper

DIRECTIONS FOR USE

1. Shake well before using.
2. To spray, can must be held upside down.
3. Hold can 6--10 inches from baseboard or surface to be sprayed.
Cover wax and soil with a thick, even coating of SFR.
4. Do not use on painted or varnished surfaces. Immediately wipe off any overspray.
5. Wait 3-5 minutes or longer in cases of severe build-up.
Then scrub the surfaces with a wet scouring pad or some type of mild abrasive pad.
6. Rinse surface clean with warm water. Allow to dry completely before recoating with floor finish.

NOTE: Before using, always test SFR on a small area of the surface to be cleaned to be sure that there is no attack. Note any change in color or texture, particularly on old tile floors.

Please review label and MSDS for all product directions, precautions and first aid information.

TECHNICAL DATA

APPEARANCE: Aerosol spray

ODOR: Morning Fresh™

FLAMMABILITY: Positive flame extension

SPRAYHEAD: Can contains special spray valve allowing application when can is turned upside down

FLOOR FINISH REMOVAL: Excellent

APPLICATION AREAS: Baseboards, corner areas, floor machines, appliances and other hard-to-strip areas

PENETRATING AGENT: Present

AMMONIA CONTENT: None

STRIPPING AGENT: Synergistic organic nitrogen compound and 2-Butoxyethanol

DELETERIOUS EFFECT ON:

Vinyl: None

Linoleum: None

Terrazzo: None

Ceramic tile: None

Stainless steel: None

Painted surfaces: May attack some paints. Test small area before use.

RINSABILITY: Excellent



State Industrial Products
5915 Landerbrook Drive
Mayfield Heights, OH 44124
To Order Call: 1-866-747-2229
www.stateindustrial.com

Canada
6935 Davand Drive
Mississauga, Ontario L5T 1L5
To Order Call: 1-800-668-6513

Puerto Rico
Royal Industrial Park, Bldg "M"
Local #5, Carr 869, km 1.5 Palmas
Cataño, PR, 00962
To Order Call: 1-800-782-2436

Part #101214

**90R03
LIT800084**

© Copyright 2009 — State Industrial Products Corp.