

# SPECIALTY *Solutions*



# SPACE JAM

Expanding Foam Sealant

- Expands to economically fill and seal large gaps and cracks
- Insulation Rating of R5 per inch, flame retardant
- Can be used indoors and outdoors



**S**tate®  
Since 1911

CARE FOR WORK ENVIRONMENTS®

# SPACE JAM

## Expanding Foam Sealant

### EXPANDS TO SEAL

Space Jam contains one component moisture-cure polyurethane insulating foam that expands 2-3 times dispensed volume. Space Jam forms an airtight barrier that provides superior insulation (R5/inch) and is water and weather resistant. When cured, it is weather and rot proof and can be sanded, painted, or stained if necessary.

### QUICK AND EASY

Space Jam dries to touch in 15-30 minutes and fully cures in 24 hours. With its pin-point tube application tube, Space Jam is easy to get into the gaps and cracks you want it in. Each can provides 800 lineal feet of 3/8" bead.

### ENDLESS USES

Space Jam is ideal for sealing wherever you need to control air leakage to prevent energy loss! Use around air vents, attics, baseboards, cable entries, windows, walls and more. Helps to keep rodents out as well.

### DIRECTIONS FOR USE:

1. Shake can vigorously for one minute. Works best if used between 65°F and 85°F.
2. Area to be foamed should be free of dirt or debris and oils or grease. Cover up surrounding areas with masking tape, paper or poly film.
3. Use protective eyewear and gloves.
4. Attach nozzle adapter on can and invert can to begin using. Press trigger slowly.
5. Do not fill cavity completely. Product will expand 2-3 times.
6. Dries tack-free in 15 - 30 minutes, fully expands in one hour, and cures in 8-24 hours depending on humidity.
7. Cured foam can be trimmed with a sharp knife or by sanding.
8. Cured foam exposed to sunlight must be covered with paint or stain.
9. When storing, leave nozzle on can and store in upright position. To reuse, cut off 1 inch from nozzle tip. Remainder of can must be used in 30 days.

Please review label and SDS for all product directions, precautions and first aid information.

### TECHNICAL DATA:

**COLOR:** Off White - Cream

**CONSISTENCY:** Frothy Foam

**SHELF LIFE:** 1 year minimum

**APPLICATION TEMPERATURE:** 65 - 85°F for best results

**INSULATION RATING:** 1" = R-5

**COVERAGE:** 800 lineal feet of 3/8" bead

### APPROVALS/STANDARDS

UL723-

- ASTM E-84 (12.5%)
- Flame Spread 25
- Smoke Developed 50

CCMC 07911

### PACKAGING

121426-12	12 OZ Aerosol/CS12
121426-24	12 OZ Aerosol/CS24



**State Industrial Products**  
5915 Landerbrook Drive  
Mayfield Heights, OH 44124  
To Order Call: 1-866-747-2229  
www.statechemical.com

**Canada**  
6935 Davand Drive  
Mississauga, Ontario L5T 1L5  
To Order Call: 1-800-668-6513

**Puerto Rico**  
Royal Industrial Park, Bldg "M"  
Local #5, Carr 869, km 1.5 Palmas  
Cataño, P.R. 00962  
To Order Call: 787-275-3185

