

GROUNDSCARE *Solutions*



STA-PATCH® ASPHALT PATCH/CHUCKHOLE FILLER

- Instantly sets
- Cold and warm weather formulas
- Provides permanent repairs



State
Since 1911

CARE FOR WORK ENVIRONMENTS®

STA-PATCH®

ASPHALT PATCH/CHUCKHOLE FILLER

INSTANT REPAIRS

Sta-Patch® repairs, patches and fills chuckholes immediately. The repaired area is then ready for traffic. No waiting for "curing" or "set-up" time. Always allow for further compression during initial traffic.

PERMANENT REPAIRS BECOME STRONGER WITH USE

Sta-Patch "sets" by compression. The pourable compound develops into a tough, durable patch when tamped. Repairs become part of the surface. Cracks, ruts, holes, broken areas, worn spots or large chuckholes are repaired quickly and permanently with a patch tougher than the original surface.

USE IN ANY WEATHER

Use Sta-Patch Warm Weather in temperatures above 50°F (10°C) and Sta-Patch Cold Weather in temperatures below 50°F (10°C). Sta-Patch can be used indoors or out, on wet or dry surfaces, and sets up as a durable, water-resistant, weatherproof repair.

EASY TO APPLY

Sta-Patch is a pre-mixed, ready-to-use compound. No messy mixing or heating is required. Simply pour into place and compress by tamping or rolling. The job is complete and ready for traffic.

ECONOMICAL TO USE

In addition to the labor savings, Sta-Patch saves time and money because it is a single patch material that can be used on most surfaces: concrete, blacktop, stone or brick.

DIRECTIONS FOR USE

Sweep loose dust, dirt and debris from surface. Large areas may be hosed with water, if necessary. Sta-Patch can be used on wet surfaces, providing there are no puddles. No primer is necessary. Store Sta-Patch indoors for at least a day prior to use in cold weather.

Apply Sta-Patch directly from the container. Fill area to be repaired slightly higher than the surface to allow for tamping down and compression from traffic.

Compress Sta-Patch by tamping, heavy roller, back of flat shovel, or other heavy object until surface is hard. Extremely deep areas should be filled with dirt and/or rock and tamped firmly to a depth of no more than 1.5 to 2 inches before application of Sta-Patch. Apply Sta-Patch in layers of one inch, tamping each layer firmly before applying the next layer.

Please review label and SDS for all product directions, precautions and first aid information.

TECHNICAL DATA

APPEARANCE: black crushed aggregate

ODOR: petroleum odor

INGREDIENTS: asphalt, crushed aggregate, wetting agents, compression agents

TEMPERATURE RANGE:

warm weather formula: above 50°F (10°C)

cold weather formula: below 50°F (10°C)

COVERAGE: 6 sq ft per pail at 1" thickness

STORAGE LIFE: up to two years

PACKAGING

26013	6 GL (#60) Drum Warm Weather
118450	6 GL (#60) Drum Cold Weather



State Industrial Products
5915 Landerbrook Drive
Mayfield Heights, OH 44124
To Order Call: 1-866-747-2229
www.stateindustrial.com

Canada
6935 Davand Drive
Mississauga, Ontario L5T 1L5
To Order Call: 1-800-668-6513

Puerto Rico
Royal Industrial Park, Bldg "M"
Local #5, Carr 869, km 1.5 Palmas
Cataño, PR. 00962
To Order Call: 787-275-3185

