

COATING *Solutions*



WTS®
WHITE CEILING TILE SPRAY



- Seals the surface
- Restores the tile
- Provides perfect color match

S **tate®**
Since 1911

CARE FOR WORK ENVIRONMENTS®

WTS®

WHITE CEILING TILE SPRAY

RESTORES AND RENEWS COST EFFECTIVELY

WTS is specially formulated to cover water stains and soil on acoustical tile and ceilings. The first application seals and the second application restores and reconditions ceilings. It's that fast and easy. WTS eliminates stains, dirt, yellowing and discoloring. There is no need to paint or replace ceiling tiles. Simply spray, let dry and ceilings look new again.

Painting ceiling tiles is cumbersome and expensive. WTS is extremely economical. One can will coat approximately 200 square feet which typically covers 8 tiles with three coats.

MAINTAINS ACOUSTICAL PROPERTIES

Latex or oil-based paints coat and seal off the sound-deadening chambers on acoustical tiles which destroy their acoustical and noise reducing properties. WTS gives ceilings a fresh, new look without destroying the ceiling tile's acoustical properties.

ADDITIONAL APPLICATIONS

WTS can also be used to seal stains and graffiti preventing bleed through. Prime with WTS and simply paint over with regular paint. No bleed through, chipping, or cracking. Works on metal surfaces, cast or poured concrete, as well as ceiling tile.

DIRECTIONS FOR USE

Please review label and SDS for all product directions, precautions and first aid information.

For best results, cover the area under the tile to be sprayed with newspaper or a drop cloth to protect from overspray. Protect areas not to be sprayed with masking tape or paper.

1. Shake can well. After ball begins to rattle, shake for an additional minute. Continue to shake can occasionally while spraying.
2. For installed ceiling tiles, hold can vertically and point top of spray button toward tile surface. Hold can 12 to 15 inches from tile. Apply several thin coats rather than one heavy coat. For ceiling tiles removed from ceiling, prop tiles up on work surface and follow same directions.
3. Apply first coat by using short, light bursts. This first coat should not cover stain completely. Apply additional thin coats until stain is completely covered. Allow a minute or two drying time between each coat. Keep hand in motion while spraying.
4. If material runs or sags, the coating is too heavy or the can is too close to tile being sprayed.
5. After spraying, turn can upside down and depress nozzle for several seconds to clean out any material left in the nozzle.

TECHNICAL DATA

APPEARANCE: white aerosol spray

COATS REQUIRED TO COVER: At least 2, thin coats

COVERAGE: 200 square feet or 8 ceiling tiles with 3 coats

NET WEIGHT PER CAN: 16 oz.

STABILITY: Minimum 1 year.

PACKAGING

| | |
|-----------|--------------------|
| 121790-12 | 16 OZ Aerosol/CS12 |
| 121790-24 | 16 OZ Aerosol/CS24 |



State Industrial Products
5915 Landerbrook Drive
Mayfield Heights, OH 44124
To Order Call: 1-866-747-2229
www.stateindustrial.com

Canada
6935 Davand Drive
Mississauga, Ontario L5T 1L5
To Order Call: 1-800-668-6513

Puerto Rico
Royal Industrial Park, Bldg "M"
Local #5, Carr 869, km 1.5 Palmas
Cataño, P.R. 00962
To Order Call: 787-275-3185

