



VEHICLE CARE
SOLUTIONS

Evolution[®]
CAR & TRUCK
WASH
General Purpose Cleaner



- Powerful cleaning action cuts through tough soils
- Advanced polymers repel dirt buildup and extend surface gloss
- Super concentrated for economical use with State's One Solution™ dilution system
- Green Seal® Certified (GS-53)



stateindustrial.com

Care For Work Environments[®]



Ecolution® CAR & TRUCK WASH

General Purpose Cleaner

PRODUCT OVERVIEW :

TOUGH CLEANER

Ecolution® Car & Truck Wash contains special cleaning agents that lift and trap dirt until it is rinsed away. Removes soil, grease, gas, stains, oil and other deposits from car and truck surfaces. Safe on plastic and all automotive finishes.

WHERE TO USE

Use Ecolution® Car & Truck Wash to clean cars, trucks, school buses and all other vehicles. It can be sprayed, sponged or brushed on soiled surfaces.

DILUTES FOR ECONOMICAL USE AND SAFE FOR SURFACE CLEANING

Concentrated Ecolution® Car & Truck Wash can be diluted to meet your specific needs. Ecolution Car & Truck Wash can be used with the One Solution™ Smart Foamer or in a high pressure unit for most effective cleaning.

SPECIALLY FORMULATED

Ecolution® Car & Truck Wash is specially formulated to eliminate water spots and produce high level suds to last throughout the job, all while remaining safe on automotive surfaces. It also provides show room finish to keep vehicles and fleets looking good. It does this with biodegradable surfactants that are more environmentally preferred compared to conventional washes. It also contains a polymer which extends gloss.

DIRECTIONS FOR USE :

Several dilution ratios are available. The One Solution™ dispensers assure accurate dispensing for optimum cost control, product performance and worker safety.

Dilute with hot water. For best results use 120°F water.

	ECOLUTION® CAR & TRUCK WASH	WATER
Heavy	6 OZ	1 GL
Medium	1.25 OZ	1 GL
Light	1 OZ	1 GL

Hose vehicle first with plain water. Apply cleaning solution with sponge, brush, foamer or pressure sprayer and agitate. Rinse and wipe dry.

Recapturing Wash Water: Keep washing activities away from storm drains and water conveyances, and do not discharge wash water to storm drains. When washing vehicles indoors or in a paved area, contain and collect wash water, and discharge the water to a suitable unpaved area or to the sanitary sewer after obtaining property owner permission and any necessary discharge permits. When washing vehicles on a pervious area, allow the water to infiltrate into the gravel or soil on site.

NOTE: Will not harm metal surfaces. Care should be utilized on painted surfaces for pressure washer applications. Light duty dilution ratio is recommended when using through high pressure washer equipment.

TECHNICAL DATA :

APPEARANCE: light amber liquid

ODOR: no fragrance added

DENSITY: 8.63 pounds/gallon

FOAMING STABILITY: excellent

USED AS HAND OR BRUSH CAR OR TRUCK WASH: yes

pH: 7.5 - 9.0 (concentrate)

SHELF LIFE: 2 years

Please review label and SDS for all product directions, precautions and first aid information.

Improper use or dilution may increase the risk of health effects.

Dispose of excess product in accordance with local, state and Federal regulations.

PACKAGING

118934	55 GL Drum
118933	20 GL Drum
124700	5 GL Pail
125589	1 GL Bottle/CS4
118930	3 L Bottle/CS4



CONTACT US

 stateindustrial.com

 support@stateindustrial.com

 1.866.747.2229

 5915 Landerbrook Drive, Mayfield Heights, OH 44124

