

stateindustrial.com



SPECIALTY SOLUTIONS



- Powerful holding strength with mechanical fastener reliability
- Interlocking self-engaging design for quick secure connections
- 2.5x stronger adhesive backing
- Durable construction resists sun UV rays and solvents



Care For Work Environments®





PRODUCT OVERVIEW:

Interlok-38 has a high-performance adhesive backing that can bond to many surfaces including but not limited to the following: Bare Metals, Structural Composites, Plastics, Polystyrene, Painted Metals, Naugahyde, Glass, ABS, Rigid Vinyl, Acrylic, Plasticized Vinyl, Fiberglass, Sealed Wood, Polycarbonate

Get the convenience and speed of a tape fastener with the holding power of a mechanical fastener.

FEATURES:

- 38 PSI push-pull holding strength (262 kPa): Holding power and reliability of mechanical fasteners such as bolts, screws, snaps, hooks, latches, etc.
- Interlocking mushroom-shaped heads: Fast assembly; Self engaging: Only one product to inventory.
- High performance adhesive: Superior bonding strength to numerous surfaces. 2-1/2 times stronger than the holding power of the product.
- Semi-permanent: Provides the convenience of conventional hook & loop fasteners Reclosable.
- Durable: Resistant to sun and Ultraviolet Rays, Resistant to solvents and aging. Holds underwater.
- Convenient: No tools required for installation. No need to drill holes.
- Adheres at temperature extremes -20° F to 158° F (-29° C to 70° C) continuous. -20° F to 200° F (-29° C to 93° C) intermittent.

APPLICATIONS:

Automobiles, Truck, RV's

- Adhere access panels to consoles
- · Mount garage door openers
- Mount electronic transponders for toll gates

Marine

· Attach boat covers

Electrical/Electronic

Affix control panels, battery packs

Miscellaneous

Mount signs or displays

- Secure First-Aid kits, remove storage (tool boxes)
- · Affix headlight covers and window louvers
- · Secure removable tackle boxes
- · Lock down accessories and equipment

• Attach components

- Secure testing devices
- · Fasten covers on equipment, machinery or vehicles

DIRECTIONS FOR USE:

Remove liner from one piece of Interlok-38 and press firmly on the surface it is to be applied to. Repeat the process for the other piece of Interlok-38. Press the two pieces of Interlok-38 firmly.

PACKAGING

124425 1 Roll (1" x 10' roll)

CONTACT US



stateindustrial.com



support@stateindustrial.com



1.866.747.2229



5915 Landerbrook Drive, Mayfield Heights, OH 44124



