




COATING SOLUTIONS

DEFENDER

Rust Treatment Paint/Paint Primer/Polymeric Coating



- Stops rust completely, does not just cover it up
- Prepares rusted surfaces for painting
- Leaves a waterproof coating that protects metal surfaces



stateindustrial.com

Care For Work Environments®



DEFENDER

Rust Treatment Paint/Paint Primer/Polymeric Coating

PRODUCT OVERVIEW :

STOPS RUST

Defender II is not a cover-up. It stops rust in its tracks and puts an end to metal deterioration. Defender II chemically reacts with rust as it is being applied to iron or steel surfaces, transforming it into stable organic metal compounds. Existing rust is converted into a firm, black surface that helps prevent further corrosion. Defender II leaves a weatherproof, polymeric coating that seals out oxygen and moisture, delivering excellent indoor and outdoor corrosion protection.

ONE-STEP PREPARATION

It is both a treatment and a primer. It provides everything you need to prepare a rusted surface for painting. Simply use a wire brush to remove loose paint, clean off grease and dirt, then apply.

CLEANS UP QUICKLY AND EASILY

Tools used to apply Defender II clean up with water and detergent. No soaking and no need for strong solvent paint thinners.

DIRECTIONS FOR USE :

Shake and stir well before using. Apply only when temperatures are between 60-100° F.

ON RUSTED METAL:

Defender II is a metal primer, not a paint. Rust removal is not required; simply remove loose or peeling paint. For best results, clean the surface with a product such as State 999® and rinse with clean water. Apply Defender II undiluted with a brush. Allow to dry overnight. Apply a second coat of Defender II or a topcoat of paint. Where rust is heavy, two coats of Defender II may be required to ensure proper penetration and coverage.

For outdoor use and maximum indoor performance, a topcoat of paint is recommended. Allow 24 hours drying time before applying topcoat.

Clean brushes with water. Avoid spreading onto adjacent areas. If splashing occurs, rinse with water.

ON NEW METALS:

For new ferrous, aluminum, or galvanized surfaces, apply two coats of Defender II. Follow the directions above for proper application. A paint finish coat may be applied over Defender II. Allow proper drying time between coats.

NOTE: Not for use on surfaces that are continuously submerged in water.

Please review label and SDS for all product directions, precautions, and first aid information.

TECHNICAL DATA :

APPEARANCE: Milky emulsion

COLOR: Off white

pH: 2.0

SOLIDS: 30%

FLASH POINT: >200°F (TCC).

COVERAGE: Approx. 600 sq. ft. per gallon

REMOVABILITY: Defender II can be removed with Floor Wizard™ High Performance Stripper or a concentrated highly alkaline cleaner. If paint is used as a top coat, paint stripper must be used to remove the coatings.

APPLICATION TEMPERATURES: 60 -100°F

DRY-TIME BEFORE PAINT: 24 hours

APPLICATION METHODS: Brush or spray equipment

SHELF LIFE: Two year


PACKAGING

123801	55 GL Drum
122485	1 GL Bottle/CS4
122483	1 QT Bottle/CS12

CONTACT US

 stateindustrial.com

 support@stateindustrial.com

 1.866.747.2229

 5915 Landerbrook Drive, Mayfield Heights, OH 44124

